with TOUCHSCRE

The new Slash-Tec™ ORRA™ DA4 (GSF) is a no glass, no steel cut resistant glove designed for use in medium cut risk areas.

This glove features a palm dip ORRA™ coating and a GSF liner. Made with a blend of enhanced HPPE, Nylon, and Spandex, this glove offers excellent protection without the use of glass or steel. The reinforced thumb crotch enhances durability, with touchscreen compatibility.



Touchscreen capable

No need to remove gloves to use touchscreens

No Glass. No Steel.

GSF means "Glass and Steel Free". Made with HPPE, Nylon and Spandex

Proprietary ORRA™ coating

High abrasion resistance, minimized particle shedding, excellent all-around grip

Reinforced thumb crotch

Offers improved durability in this area

Enhanced comfort and tactility

GSF Liner, ORRA™ coating and ergonomic former add up to create a comfortable, flexible and form-fitting experience

The touchscreen feature of the device, if present, must be turned on and adjusted. Since the gloves have conductive properties, do not use in areas that have a potential risk of static discharge and electric shocks. Performance of touchscreen functionality may vary due to temperature and humidity. Touchscreen compatibility depends upon the type of device, sensitivity of device, the way the device is operated, ambient conditions, type of coating and fitting of the glove.

Style Code	BC5P-3HMPXX-OC-XX-SIZE(TCD) (TS)
Glove Name	Slash-Tec™ ORRA™ DA4 (GSF)
Sizes	XS,S,M,L,XL,XXL
Liner	HPPE, Nylon and Spandex blend
Liner Color	Sky Blue or Royal Blue
Coating	ORRA Comfort Foam Technology
Dip Levels	Palm Coating
Coating Color	Black

Sanitiged- Actifresh	The coating on these gloves is treated with Sanitized® antimicrobial material protection and odor-reducing technology. Sanitized® will not protect the wearer of this garment against disease-causing bacteria.

Abrasion		0	1	2	3	4					
Tear	EN388: - 2016 - +A1:2018	0	1	2	3	4					
Puncture		0	1	2	3	4					
Cut (TDM)		-	Α	В	С	D	Е	F			
Cut	ASTM F2992		A1	A2	А3	Α4	A5	A6	A7	A8	A9
Abrasion (Taber)	ASTM D3389	-	1	2	3	4	5	6			
Puncture	ANSI/ISEA 105 - 2016	-	1	2	3	4	5	6			















The new Slash-Tec™ ORRA™ DA4 (GSF) is a new medium cut risk protection glove, designed for ultimate safety without the use of glass or steel. This glove features a palm dip ORRA™ coating and GSF liner. Made with a blend of HPPE, Nylon, and Spandex, it offers reinforced protection in the thumb crotch

area. Plus, enjoy touch screen compatibility.

SLASH-TECTM

TECHNOLOGIES

Touchscreen

TRUE VALUE OF THIS GLOVE

A no glass, no steel cut resistant glove for protection in medium cut risk areas.

KEY MARKETS AND APPLICATIONS

Automotive manufacturing, intricate assembly, sheet metal operations, injection molding operations, glass and ceramics handling

SLASH-TEC™ ORRA™ DA4 (GSF)

EN388:2016 +A1:2018

Abrasion

ANSI/ISEA 105 - 2016 **Puncture**

BC5P-3HMPXX-OC-XX-SIZE(TCD) (TS)

4X42D

A4 /1600 5/>12,500 (In-house) (In-house)

(In-house)

Machine knitted HPPE composite construction liner with ORRA™ palm coating. Touchscreen through coating. Sizes: XS,S,M,L,XL,XXL
















MIDAS SAFETY AND SUSTAINABILITY

Supporting the United Nations' Sustainability Development Goals (SDG), we have finalised our targets for 2023 around seven pillars; People, Climate, Water, Energy, Waste, Product and Packaging















